

STEEL ROOF RACKS

SAFETY AND FITTING NOTES

2.2 METERS STEEL ROOF RACK 220 X 120 X 25 CM	1.8 METERS STEEL ROOF RACK 180 x 125 x 17 cm
<p>FREE UK POSTAGE !</p> <p>UK SELLER  IN STOCK</p>  <p>25 cm</p> <p>220 cm (2.2 Meters) 7ft+</p> <p>125 cm</p> <p>CAPACITY 300 Kg +</p> <p>LARGE STRONG STEEL (POWDER COATED) ROOF RACK</p>	
<p>YOUR ROOF RACK WILL BE SUPPLIED WITH STANDARD NORMAL 16 CM STANDARD BRACKETS. QUANTITY 8 SETS</p> <p>STANDARD BRACKETS</p>  <p>6 inch 16 cm</p> <p>3.5 INCH 9 CM</p> <p>CLICK SUPERSTORE</p>	<p>YOUR ROOF RACK WILL BE SUPPLIED WITH STANDARD NORMAL 16 CM STANDARD BRACKETS. QUANTITY 6 SETS</p> <p>STANDARD BRACKETS</p>  <p>6 inch 16 cm</p> <p>3.5 INCH 9 CM</p> <p>CLICK SUPERSTORE</p>



LONGER 26 CM BRACKETS ARE AVAILABLE SEE PICTURE ON THE LEFT

FOR AN EXTRA CHARGE FOR LONG HIGH TOP VEHICLES

ALTERNATIVELY WE CAN SUPPLY EXTRA EXTENSION BRACKETS AS SHOWN BELOW AT A SMALL COST



ABOVE PICTURE - 16 CM STANDARD BRACKETS



ABOVE PIC - 26 CM LONGER BRACKETS



SOME EXAMPLES OF HOW IT LOOKS ABOVE



SOME EXAMPLES OF HOW IT LOOKS ABOVE

	
<p>SOME EXAMPLES OF HOW IT LOOKS ABOVE</p>	<p>SOME EXAMPLES OF HOW IT LOOKS ABOVE</p>
	<p>These pictures on the left and below show how the bracket fits on to your ridge / gutter</p> <p>The grips must be tightened to your gutter ridge both from the outside and the inside</p> 

Notes:-

Before you buy the product you must measure your roof and check this against the measurements of the rack to ensure it will fit. Your vehicle must have ridges or gutters in order to fit this product. The brackets do allow a small amount of adjustment both horizontal and vertical. These notes are by no means a comprehensive guide to all aspects of the rack but are designed to bring to your attention some of the aspects involved in fitting and using the rack. No fitting tools are supplied. We do have available lighter aluminium racks which are smaller at about 1.2m for smaller vehicles.

- 1) This is a very heavy duty steel roof rack and cannot be handled by one person. There must be at least two persons and we recommend 4 to carry it, fit it and lift it
- 2) Safety is of paramount importance. If this roof rack is not lifted or carried or fitted properly it can cause serious injury. It is the responsibility of the buyer to ensure that they are carrying it, lifting it and fitting it properly
- 3) Do not drive the vehicle before checking that the rack is completely secure. This must be done before every journey

- 4) Check that all the brackets are fully tightened. It may be that tightening one side may make the other side loose so one needs to go around again and again making sure all sides are tight
- 5) The rack must not protrude outside the parameter of the vehicle. It can cause head injury to passers-by if it protrudes outside the boundary of the vehicle and can cause motor failure. The rack can be smaller but not bigger than the overall boundary of your vehicle
- 6) Do not rely on the basket or border of the rack to hold secure any boxes or items being carried. Always secure further with ropes or elasticated straps
- 7) Do not overload your vehicle.
- 8) Ensure that the rack is even and straight and is central and in the middle of the vehicle both horizontally and vertically
- 9) The front of the rack must be facing the direction of travel.
- 10) Off road lights fitted on the rack must not be used on the road as they can cause temporary blinding of other road users
- 11) If you are not sure of the fitting do take it to a garage and get some professional help and assistance in fitting .
- 12) Children and pets must be kept away and under no circumstances must children be allowed into the fitting and storage area
- 13) Until the rack is secured from both sides it will not be secure and can slide down the other side. The grips only work when both sides are together tightened and pushed against each other. Hence several people are required to hold the rack from the other side whilst it is being secured.
- 14) A lot of care must be taken whilst lifting and carrying this rack. A slight hit against a window will break the window and if it is roughly handled it can cause scratches on the roof or side of the vehicle. We do not take any responsibility for any such damage
- 15) The entire process of lifting, fitting, carrying and driving is the responsibility of the buyer. No liability will be entertained for any damage or injury directly or indirectly associated with this rack.
- 16) These are universal generic racks and we are not agents for any vehicle manufacturers or brand names. These are aftermarket compatible unbranded universal type of products.
- 17) After every period of use, do check the rack again and again . Check that the bolts are secure and the brackets and the ridges/gutters are not corroded or worn and that the roof is stable and straight.
- 18) Ensure that your vehicle roof is strong enough to carry the weight of this rack which is in the region of 37 kg and that it can further carry the goods that you are putting on it. Weak and unsupported vehicle roofs may sag or bend and no responsibility is accepted for the same.
- 19) Any variations to the design and fitting are the responsibility of the buyer and user. The extra-long brackets and the extension brackets are not designed for heavy use and may make the rack less stable therefore extra care and checks must be carried out to ensure it is safe and secure.
- 20) The brackets must be secured against the ridge or gutter and grip the gutter from both above and below. The rubber sheath or border must be used to improve the grip and prevent scratches. Over time this may become loose and must be checked frequently.