

## **WHEEL COVER FITTING & SAFETY INSTRUCTIONS**

**\* DO NOT PEEL OFF THE PROTECTIVE ANTI SCRATCH FILMS OR PUT A VINYL STICKER ON UNTIL YOU HAVE CHECKED THAT IT FITS \***

There are over 255 sizes for 4x4s & Vans divided into 24 Groups. Each ring fits 10 sizes within its group for example a ring of diameter 27 inches & width 8.4 inches (Group 3) would fit both 215/65/16 as well as 215/70/15 as they are both exactly the same diameter & width. Therefore please do not assume you have the wrong size if you see that the writing on the box or disc is different. This is a complex bespoke product - not an off the shelf standard item so please bear with us if you have an issue.

**WATCH THE HOOK** – Please ensure that the hook part of the closing latch does not catch on the edge of the actual ring but sits firmly in the locking slot. Forcing the lever with the hook catching the rubber or edge can break & damage the ring edge. This will be visible upon return & in such instances no refund or replacement will be made.

**DENTS** In the rare instance where there is a small dent on the wheel please be fair and do try to remove it first by means of a firm push from the underside. Just put the wheel on a carpet & gently push out the dent from the inside using the heel of your foot or hand carefully. Garages have a dent pulling suction puller & this can also be used if it's a big dent. In extreme damage cases we will assist to lodge a claim with the couriers & will need photographs emailing to us showing the dent within 7 days **IF IT DOES NOT FIT PLEASE TRY THE FOLLOWING FIRST:-**

- *Check your Tyre pressure; if it's loose it may require increasing or decreasing.*
- *Is your tyre worn or brand new? (sometimes it may be easier to swop tyres)*
- *You can LEAVE A GAP between the two edges if the ring appears too short*
- *You can also OVERLAP the two edges of the rings if the ring appears too big*
- *In some cases you can put your old soft cover on the tyre to grip the ring better or use some leather padding strip to assist. Be careful to check that it is firm.*
- *The width of the ring may be a little smaller or a little wider & that is also acceptable & normal due to the fact that there is a bend a curve at the edges*
- *Check that the tyre size of your spare tyre is the same as the other four tyres!*
- *Try the RING ONLY first without the centre disc. It could be the centre disc thats stopping you from closing the ring. The edges of the centre disc can be gently rubbed down /grinded to reduce the size by a mm or two.*
- *Note that there are two locking adjustments. The hook slots plus a fine tuning adjustment underneath where you can revolve the bracket round to adjust.*

**EXCHANGE & RETURN** - We will assist in exchanging the cover where the size is incorrect or it has been damaged badly beyond repair in transit within 7 days. In the event that you gave us the wrong size we will only charge for the carriage. We recommend [www.parcel2go.com](http://www.parcel2go.com) who only charge 5.99 via DHL Yodel etc 2-3 days collection to collect the box from your house & deliver it to us) Returns must be within 7 days & by prior arrangement only at the cost of the buyer in the original box with the centre disc & keys . If you leave negative feedback quickly before contacting us we will not assist you - We prefer to resolve all issues amicably & honestly.

### **SAFETY & MAINTENANCE**

**This is a metal product & may have sharp edges - Mind your hands & wear gloves.** Please regularly check the tightness of your tyre cover. If this is loose or the lock is faulty **do not use it** on the road. Remember to keep your keys safe. Children should be kept away. Use a light oil spray or wax /polish regularly to keep your ring shiny & make sure the lock is at the bottom to ensure water drainage. Avoid high intensive action automatic car washes. If your ring gets scratched & as it gets older over the years you can colour paint the surface, or underside or disc. **No liability for damage or injury either directly or indirectly is accepted & it is the sole responsibility of the vehicle user & owner to ensure that the item is firmly attached does not cause damage or injury to any person or persons.**